

Builder's Level of the F-Series

Budget-priced builder's levels for the use on construction sites

Also available as a kit



®

Precise surveying
and measuring

F28



F32



Technical data:

Optics	upright	upright
Magnification	28 x	32 x
Lens diameter	30 mm	40 mm
Shortest focusing distance	0.6 m	0.6 m
Multiplication factor	100	100
Compensator operating range	± 15'	± 15'
Adjusting accuracy	± 0.3"	± 0.3"
Circular graduation	400 gon	400 gon
Sensitivity of circular bubble	8' / 2 mm	8' / 2 mm
Standard deviation for 1 km double-run levelling	± 2.0 mm	± 1.5 mm
Weight	1.26 kg	1.26 kg
Connecting thread	5/8"	5/8"
Ref.-No.	460 795-613	460 797-613

Also available as a kit



The levels F28 and F32 are also available as a kit including a 5 m telescopic levelling staff and an aluminium tripod.

Kit F28 Ref.-No. 465 105

Including Builder's Level F28.....460 795-613
 Telescopic levelling staff.....345 115-613
 Aluminium tripod.....200 215-613

Kit F32 Ref.-No. 466 105

Including Builder's Level F32.....460 797-613
 Telescopic levelling staff.....345 115-613
 Aluminium tripod.....200 215-613



®

Precise surveying and measuring

Nedo GmbH & Co. KG

Hochgerichtstrasse 39 - 43 · D-72280 Dornstetten

Phone: +49/7443/2401-0 · Fax: +49/7443/2401-45

www.nedo.com · info@nedo.com

Your Nedo Dealer